INTRODUCING THE REAL ALITHERM 400 SYSTEM









Alitherm 400 is our premium system. It's manufactured incorporating an extruded glazing gasket, which serves to enhance performance and improve installation time. As the first of its kind to be built into a thermally broken aluminium system, it combines outstanding quality and value with leading class performance and security.

Its innovative design features polyamide thermal break technology that significantly reduces thermal transmittance by creating a barrier between the cold air outside and warm air inside, enhancing the systems overall 'U' value. The system is also rigorously tested to PAS 24:2016 as standard and exceeds the requirements for weather resistance and security performance.

Document L Compliant:

Changes to Document L and F of the Building Regulations in England were introduced on the 15th June 2022, to ensure all new and renovation projects are on-spec for thermal efficiency, energy efficiency and ventilation capability.

Our Alitherm 400 aluminium system is manufactured using the highest quality and have been specifically engineered to meet the new Document L regulations. We have also compiled specific product documentation that will help you understand what is required to be compliant with the new regulations.



You can view or download the document now at re-aluminium.co.uk

Alitherm 400 Windows

Alitherm 400 windows are currently available in two options. The popular Alitherm 400i range is an internally beaded system with dummy sashes which can achieve PAS 24 security standards. Alternatively, we have the externally glazed Alitherm 400x range, which can be upgraded to PAS 24 security standards with the introduction of glass security clips.



Window Type	Maximum Width (mm)	Maximum Height (mm)	Frame Depth (mm)	Maximum Perimeter (mm)	Glazing Units	Security Standard	Air Permeability Classification	Water Tightness Classification	Resistance to Wind Classification			
Sash dimensions for windows with approved sash profiles:												
Side Hung	864	1400	70	-	28, 40	PAS 24:2016	Class 4	E1200	AE2400			
Top Hung	1400	1500	70	-	28, 40	PAS 24:2016	Class 4	E1200	AE2400			
Fixed	2100	2100	70	42	28, 40	PAS 24:2016	Class 4	E1200	AE2400			

Note: Alitherm 400x windows require wedge gasketing

Alitherm 400 Doors

Suitable for both residential and commercial applications, Alitherm 400 doors perfectly complement the Alitherm 400 window range, offering the same stylish lines and same ease of fabrication and installation. With unrivalled thermal performance and security assurance, the system is available as open-in or open-out, single or double doors.



Door Type	Maximum Width (mm)	Maximum Height (mm)	Frame Depth (mm)	Glazing Units	Security Standard	Air Permeability Classification	Water Tightness Classification	Resistance to Wind Classification			
Sash dimensions for doors with approved sash profiles (double door dimensions include both sashes):											
Single Door Open In	1100	2400	70	28, 40	PAS 24:2016	Class 2 300Pa	Class 5A 200Pa	Class BE 2400Pa			
Double Door Open In	2200	2400	70	28, 40	PAS 24:2016	Class 2 300Pa	Class 5A 200Pa	Class BE 2400Pa			
Single Door Open Out	1100	2400	70	28, 40	PAS 24:2016	Class 2 300Pa	Class E 1050Pa	Class AE 2400Pa			
Double Door Open Out	2200	2400	70	28, 40	PAS 24:2016	Class 2 300Pa	Class E 1050Pa	Class AE 2400Pa			



Alitherm Quick-Glaze Bead

Alitherm 400 isn't just beautiful – it's clever. With an innovative Quick-Glaze Bead system on internal glazing, you can simply tap the bead in on-site with the gasket already in place. No wedge gaskets – just a faster, simpler and more costeffective glazing process.

Alitherm Quick-Glaze Bead is available in stock colours White (WP), Black (BL) and Anthracite Grey (KL005).

Note: Wedge gaskets are required on the Alitherm 400x externally glazed range.



Alitherm 400 WINDOWS





Alitherm 400 DOORS





At a glance:

- Fully compliant with changes to document L of the building regulations
- Improved thermal and weather performance
- Brand new quick glaze bead for a simpler, faster and cost-effective glazing process
- PAS 24: 2016 approved for added security
- Unlimited colour choice provided by any RAL colour on top of the 4 stock colour collections



REAL Service. REAL Support.

From the point of placing your customer's order, our dedicated and committed team is on hand to ensure it's processed efficiently and professionally, whilst keeping you informed along the way until you receive your beautiful REAL Aluminium windows or doors ready for installation. With REAL, you'll have the customer and technical support you need from start to finish – and in the future.




In stock, ready to deliver.

Each and every product within the REAL Aluminium range is manufactured from stocked profile and components. Should there be any requirements for replacements or remakes these can be turned around in 1 week, compared to 3 weeks or more for non-stocked products.



Marketing support

Our Marketing Team are happy to support you and are on hand to help - contact them on 01453 826884 or email marketing@customade.co.uk.







Choice in aluminium

Founded in 1980, Customade Group has grown to become the well-respected market leading business it is today, delivering high-quality fenestration solutions to the construction industry. We are a collective, designed to provide you with a complete solution for your customers' projects through our specialist businesses – which includes REAL Aluminium.

Our Aluminium Division comprises REAL Aluminium, Atlas Glazed Roof Solutions, and Fineline Aluminium – specialist in their own right to bring you the very best in Aluminium doors, windows, bi-folds and glazed roof systems.

REAL ALUMINIUM. THE FINER CHOICE.

For more information, or to make your next project a REAL project, get in touch with the team at re-aluminium.co.uk



www.re-aluminium.co.uk

01453 826884 enquiries@real-aluminium.co.uk

REAL Aluminium, Newton Centre, Brunel Way, Stroudwater Business Park, Stonehouse, GL10 3SW

The information provided in this publication is provided 'as is' in November 2022. REAL Aluminium may modify and change the information and specifications from time to time for a variety of reasons, without prior notice and updates will not be issued automatically. Due to the limitations of the processes of printing or digital display of colours, no liability can be accepted for the accuracy, they are intended as guidance only. The information is not intended to have any legal effect, whether by the way of advice, representation or warranty, expressed or implied. All rights reserved. Copyright in this publication belongs to REAL Aluminium, and all such copyright may not be used, sold, copied or reproduced in whole or part in any manner in any media to any person without prior consent. Copyright ©2022 REAL Aluminium. All rights reserved.



V2 - NOV 2022 www.customade.co.uk